

CMX382 Hanging condenser microphone

Highlights:

- · 3 meter fixed connection cable
- · Phantom power adapter included
- · Flexing gooseneck structure for highly accurate positioning
- Spiral hanging bracket
- High quality back electret condenser capsule with cardioid pickup pattern

Product information:

The CMX382 is a hanging condenser microphone with a slim and miniature design. It is designed for offering versatile solutions for sound reinforcement or recording systems in a wide variation of applications. Typical applications range from speech in meeting or conference rooms to music in houses of worship, orchestra's, choirs and many others. The tailored frequency response guarantees a rich, clear and sensitive sound reproduction while the cardioid directivity characteristic eliminates feedback and unwanted noise. The included spiral hanging bracket makes overhead suspension possible above conference tables, choirs, orchestra's, ... while the flexing gooseneck structure allows a highly accurate positioning. The microphone comes delivered with a fixed connection cable with a total length of 3 meters which is fitted with a 4-pin Mini-XLR connector. An included phantom power adapter with standard 3-pin XLR connector converts the supplied phantom voltage and allows connection to standard pre-amplifiers or mixers. The included windscreen reduces unwanted and popping sounds. In comparison with the already known CMX380 microphone, the CMX382 contains an improved spiral hanging bracket and a flexing gooseneck structure which makes highly accurate positioning possible. The included phantom power adapter with low-noise characteristics guarantees improved overall signal/noise performance

Applications:

- Corporate
- Houses of worship



System specifications:

Microphone	Туре	Back electret condenser
	Connection	4-pin mini XLR
Polar Pattern		Cardioid (unidirectional)
Frequency	Response (± 3 dB)	50 Hz - 18 kHz
Sensitivity (1W/1m)		42 dB ± 3 dB / Pa
Impedance		200 Ω
Sound Pressure (Max. W/1m)		130 dB
Signal / Noise		75 dB
Power	Supply	10 ~ 52 V DC Phantom Power

Product Features:

Accessories	Included	Windscreen (MWS380/B)
		Phantom Power adapter
		Spiral hanging bracket
Dimensions		13.5 x 160 mm (Ø x L) (3 m fixed connection cable)
Weight		0.100 kg
Colours		Black
Phantom adapter	Connection	3-pin XLR

Variants:

- CMX382/W Hanging condenser microphone -white
- CMX382/B Hanging condenser microphone -black

Shipping & Ordering:

Packaging	Cardboard box
Shipping weight & volume	0.120 kg - 0.0007 Cbm

Acoustical data graphs:

Polar pattern:

