

135 LB

Full range driver unit



The 135 LB is a real full range functioning without bicone. Resulting from the control of the treatment of membrane of the Supravox laboratory the response curve of this membrane extends until 18kHz. optimization from the couple membrane/bobine made it possible to gain in speed of membrane and of sensitivity while pushing back until the limit of audible the high cut of the transducer. These parameters make of it a high speaker bafflable in volumes even more reduced than its precedent. In the Supravox column dedicated to 13 cm its answer is stable with +/- 3 dB of 60Hz with 18 Khz. 13 cm has to privilege for the ones in love with a clear and precise medium.

Mesurement curves

[Page 1](#)

[Page 2](#)

135 LB Specifications

Efficiency 1 W/1m at Fs	95 dB	Fs	80 Hz
Frequency response	80 à 18kHz	Qts	0.3
Impedance	8 ohms	Qe	0.3
Power max. RMS	35 W	Qm	3.6
Weight	1.7 kg	Vas	14 L
Suspension	5 plis papier	Bl	5.4
Linear excursion	6 mm	Re	5.2
Magnet diameter	96 mm	Cms	1
Magnetic field	1.4 T	Mms	3.3 g
Diameter HP	134/151 mm	Sd	86.5 cm ²
Frame thickness	Tôle 5mm		
Diameter fixation holes	140 mm		
Diameter drilling enclosure	122 mm		
Depth HP	80 mm		